

A simple solution to improve data capacity over satellite.

Now Nera WorldCommunicator users can achieve higher satellite data rates with the Nera Bonding Cable solution.

At a glance

- Achieves 128 kbps data rate using two Nera WorldCommunicator units
- Easy plug and play
- Full internal functionality
- Supports all standard ISDN data switched services



NERA

enabling a wireless future

Nera WorldCommunicator – ISDN 128 kbps Bonding Cable Solution

Nera has created a simpler way to achieve 128 kbps data connections, enabling Nera WorldCommunicator users to send and receive video quality communications and large file transfers.

The Nera Bonding Cable solution requires no external device or internal PC cards. Users can simply connect two Nera WorldCommunicators and instantly increase their data communication speed.

This elegant and highly effective solution is standard with new terminals, from modem revision 4.0.

A simple upgrade is available for existing terminal users at the nearest Regional Service Centre or Distributor.

Technical Specifications Bonding Cable

Length of Cable: 1.2m
Connector Type: 9 pin DSUB (Male – Male)
Cable P/N: 104653
Modem Software Release 5.5 / Modem Hardware Revision 4.0 needed

ISDN Interface: Max Cable Length 100m (ITU spec 1.430)

Connector: RJ45
Standard: Euro ISDN (DSS1), NI-1 (US)
Power Feed: Max drain 2.5 W
Impedance: 100 Ω int.



Nera

PO Box 91, N-1375 Billingstad, Norway
Tel: +47 67 24 47 00 Fax: +47 67 24 46 21
e-mail: nera@nera.no
www.nera.no